



Specifications

Compatible with Model	17, 17F, 17FV, 17FVB, 17HP, 17HPV, 17V, 18, 18-90, 18HP, 18P, 18V, 26, 26F, 26FV, 26FVB, 26HP, 26HPV, 26V, 301525, 301526, CS410A, HW-17, HW-17F, HW-17R, HW-18, HW-18R, HW-26, HW-26F, HW-26R, PTA-17, PTA-17F, PTA-17FV, PTA-17V, PTA-26, PTA-26F, PTA-26FV, PTA-26V, PTW-18, WP-17, WP-17-PSH, WP-17F, WP-17FV, WP-17V, WP-17V-PSH, WP-18, WP-18SC, WP-18V, WP-26, WP-26F, WP-26FV, WP-26V, WP-R17F, WP-R17FV, WP-R26F, WP-R26FV
Compatible with Series	17, 18, 26, A-150, A-200, A-250, HW-17, HW-18, HW-26, PTA-17, PTA-26, PTW-18, W-350, W-400, W-410
For Maximum Electrode Diameter	0.0938 in
Material	Alumina
Nozzle Nominal Size	No. 12
Reference Number	10N44
TIG Torch Application	Non-Gas Lens
Type	Standard Nozzle
Welding Processes	TIG Welding (GTAW)
Compatible with Brand	Miller
Compatible with Grainger Part Number	6XXN2, 6XXN3, 6XXN4, 6XXN5, 6XXN6, 6XXN9, 6XXP0, 6XXP1, 6XXP6, Not Found
Outside Diameter	#12 (3/4 in)
Nozzle Length	Standard
Sub-Brand	Weldcraft
Weight	0.340194 KG
Weight	0.340194 KG

