



Specifications

Nominal Dial Size	4 1/2 in
Accuracy	+/-0.5%, +/-0.5%
Gauge Case Material	Stainless Steel
Process Connection Type	NPT
Process Connection Gender	Male
Lens Material	Glass
Process Connection Size	1/4 in
Field Fillable	No
Process Connection Location	Bottom
Case Color	Silver
IP	NEMA Rating / Not Rated
Primary Pressure Range	30 to 0 to 300
Dry Dampening Feature	None
Vibration Resistance	None
Dial Color	White
Pressure Gauge Type	HVAC Dial Pressure Gauge
Liquid-Filled Case	No
Gauge Case Liquid	None
Panel-Mountable	No

Compatible Process Media	Non-Explosive Gas Or Liquid That Do Not Crystalize And Corrode Copper Alloy
Socket Material	316L Stainless Steel
Sensor Material	316L Stainless Steel
Application	General Purpose
Primary Scale Units	in Hg/psi
Accuracy Scale	Full Scale
Ambient Operating Temperature Range	-40 Degrees to 140 Degrees F
Blowout Safety Back	Yes
Cleaned for Oxygen Service	No
Freeze Resistant Movement	No
Hazardous Location Rating	Not Rated
Includes	Blow Off Disc
Includes Calibration Certificate	No
Includes Mounting Hardware	No
Includes Vent Plug	No
Non-Sparking	No
Pressure Range Type	Compound
Primary Scale Minor Graduations	1
Removable Bezel	No
Scale Type	Single
Standards	ANSI
Weight	0.83 KG
Weight	0.83 KG