



Specifications

Air Consumption	32 cfm
Air Inlet	1/2 in NPT Female
Air Pressure	90 psi
Max. Air Pressure	100 psi
Min. Air Pressure	90 psi
Min. Hose Size	1/2 in
Exhaust Location	Bottom
Duty Rating	Industrial Duty
Breakaway Torque	1,350 ft-lb
Fastening Torque	1,100 ft-lb
Free Speed	7,000 RPM
Impact Rated	Yes
Impact Sound Level	96 dB
Impacts per Minute	1,150
Number of Speed Settings	4
Power to Weight Ratio	182.4 ft-lb/lb
Max. Bolt Capacity	3/4 in
Drive Size	3/4 in Square
Drive Type	Standard

<b>Retainer Type</b>	Friction Ring, Through Hole
<b>Clutch Style</b>	Twin Hammer
<b>Tool Style</b>	Compact
<b>Vibration Level</b>	8.7 m/sq sec
<b>Overall Length</b>	8 1/2 in
<b>Handle Material</b>	Composite
<b>Housing Material</b>	Composite
<b>Handle Type</b>	Pistol Grip
<b>Tool Brand</b>	Ingersoll Rand
<b>Features</b>	Max Durability, Max Power, Max Productivity
<b>Tool Weight</b>	7.4 lb
<b>Standards</b>	EN ISO 11148-6, EN ISO 15744, EN ISO 28927-2
<b>Weight</b>	3.35 KG
<b>Weight</b>	3.35 KG