

	 <p>Air Powered, Impact Wrench, 90 psi, 425 ft-lb Fastening Torque</p> <p>Brand: Ingersoll Rand SKU: 231C Warranty: 0</p>
-----------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Specifications

Air Consumption	22 cfm
Air Inlet	1/4 in NPT
Air Pressure	90 psi
Max. Air Pressure	100 psi
Min. Air Pressure	90 psi
Min. Hose Size	3/8 in
Exhaust Location	Bottom
Duty Rating	General Duty
Breakaway Torque	600 ft-lb
Fastening Torque	425 ft-lb
Free Speed	8,000 RPM
Impact Rated	Yes
Impact Sound Level	99 dB
Impacts per Minute	1,200
Number of Speed Settings	6
Power to Weight Ratio	103.4 ft-lb/lb
Max. Bolt Capacity	1/2 in
Drive Size	1/2 in Square
Drive Type	Standard

Retainer Type	Friction Ring
Clutch Style	Twin Hammer
Tool Style	Full-Size
Vibration Level	6.5 m/sq sec
Overall Length	7 1/4 in
Handle Material	Aluminum
Housing Material	Aluminum
Handle Type	Pistol Grip
Features	Built to withstand harsh environments, Deliver the Same High-Quality Output Time
Tool Weight	5.8 lb
Standards	EN ISO 11148-6, EN ISO 15744, EN ISO 28927-2
Weight	2.63 KG
Weight	2.63 KG