



**Air Powered, Impact Wrench, 90 psi, 600 ft-lb
Fastening Torque 4Z942**

Brand: Ingersoll Rand

SKU: 2705P1

Warranty: 0

Specifications

Air Consumption	4 cfm
Air Inlet	1/4 in NPT
Air Pressure	90 psi
Max. Air Pressure	100 psi
Min. Air Pressure	90 psi
Min. Hose Size	3/8 in
Exhaust Location	Bottom
Duty Rating	Industrial Duty
Breakaway Torque	600 ft-lb
Fastening Torque	600 ft-lb
Free Speed	8,500 RPM
Impact Rated	Yes
Impact Sound Level	99 dB
Impacts per Minute	1,200
Number of Speed Settings	Continuous
Power to Weight Ratio	106.5 ft-lb/lb
Max. Bolt Capacity	1/2 in
Drive Size	1/2 in Square
Drive Type	Standard

Retainer Type	Pin Detent
Clutch Style	Twin Hammer
Tool Style	Full-Size
Vibration Level	6.5 m/sq sec
Overall Length	7 1/4 in
Handle Material	Aluminum
Housing Material	Aluminum
Handle Type	Pistol Grip
Tool Brand	Ingersoll Rand
Features	Jumbo Hammer Mechanism, Pressure Fed Mechanism Lubrication, Steel Hammer Case
Tool Weight	5.6 lb
Standards	EN ISO 11148-6, EN ISO 15744, EN ISO 28927-2
Weight	2.54 KG
Weight	2.54 KG