APTOOLS
Arab Pros For Machinery & Equipment

Product Catalog
2026-11-15 03:28 AM
www.aptools.sa

Contact: 0552822719
sales@aptools.sa
Al Shati, Dammam, Saudi Arabia

4 Piece Combo Kit: Impact Wrench, Impact Socket Set, Battery Charger, Hydraulic Hand Pump With Cylinder

Brand:
SKU:
Warranty:

Specifications

Makita DTW300RTJ Cordless Impact Wrench	
Fastening Capacities	Standard Bolt : M10 - M20
Fastening Capacities	High strength Bolt : M10-M16
Square Drive	12.7 mm (1/2 in)
No Load Speed (RPM)	0-3.200/0-1.7000/0-1.300/0-1.000
Impact Per Minute (IPM)	0-4.000/0-2.200/0-1.700/0-1.300
Max fastening Torque	330 N m (240 ft.lbs)
Dimensions (LxWxH)	144x81x246 mm
Net weight	1.8 kg
Makita B-55762 Impact Socket Set	
TYPE	1/4 inch Hex (NZ)
SHANK TYPE	NZ-B
SIZE	SQ 1/2 inch
FOR	Impact Drive
PER PKG	9pcs
Fimer CB650 Battery Charger and Starter	
Mains voltage	50/60Hz 1x230 V - 1 PH
Output voltage	12-24
Ram-Pac RC-25-SA-6, HP-50 Hydraulic Hand Pump	
Cylinder Cap. (Tons)	25
Stroke (In) "D"	6 1/4
Model Number	RC-25-SA-6
Closed Height "C"	10 3/4

Ext. Height (In)	17
Eff. Area (Square Inch)	4.90
Oil Capacity (Cubic Inch)	30.6
Outside Diameter "A"	3 3/8
Rod Diameter "B"	2 1/4
Bottom to Port Diameter "E"	1
Plunger Thread	1 1/2-16 x 9/16
Collar Thread "F"	3 5/16-12 x 2
Mounting Holes "G"	(2) 1/2-13, 2 5/16 Dia.B.C. HP-50
Oil Capacity (Cubic Inch)	37
Type of Cylinder	Single Acting
Handle Length (In)	22
Length (in)	19 3/4
Width (in)	5
Height (in)	5 1/2
Weight (lb)	16
Rated Pressure 1st Stage (psi)	N/A
Rated Pressure 2nd Stage (psi)	10,000
Oil Displacement per Stroke 1st Stage (Cubic Inch)	N/A
Oil Displacement per Stroke 2n Stage (Cubic Inch)	.19
Weight	44.3 KG
Weight	44.3 KG