

	 <p><b>Micrometer Torque Wrench, 1/2 in</b></p> <p>Brand: Proto SKU: 426F10 Warranty: 0</p>
---	--

**Specifications**

Torque Measurement Type	Foot-Pound, Newton-Meter
Drive Size	1/2 in
Torque Range	55.3 ft-lb to 261.8 ft-lb, 70 N-m to 350 N-m
Torque Increments	1 ft-lb, 1 N-m
Primary Scale Minimum Torque	70 N-m
Primary Scale Maximum Torque	350 N-m
Head Type	Standard
Secondary Scale Minimum Torque	55 ft-lb
Secondary Scale Maximum Torque	262 ft-lb
Ratcheting	Yes
Rotation	Clockwise and Counterclockwise
Torque Adjustability	Adjustable
Clockwise Accuracy	+/- 4%
Counterclockwise Accuracy	+/- 6%
Corrosion Resistant	Yes
Torque Limiting Mechanism	Click-Type
Torque Setting	Adjustable
Visual	Audible Indicators / Audible Click
Finish	Chrome

<b>Material</b>	Alloy Steel
<b>Handle Type</b>	Knurled
<b>Handle Material</b>	Alloy Steel
<b>Handle Color</b>	Silver
<b>Dual Scale</b>	Yes
<b>Min. Arc Swing</b>	15 Degrees
<b>Min. Number of Cycles</b>	5,000
<b>Number of Geared Teeth</b>	24
<b>Overall Length</b>	26 1/4 in
<b>Overall Width</b>	1 3/4 in
<b>Includes</b>	(1) Case
<b>Standards</b>	ASME B107.300-2010
<b>Weight</b>	5.9 lb
<b>Head Movement</b>	Ratcheting
<b>Weight</b>	2.7 KG
<b>Weight</b>	2.7 KG