



**Specifications**

<b>Drill Bit Size</b>	13/32 in
<b>Decimal Equivalent</b>	0.4063
<b>Measurement System</b>	Fractional Inch
<b>Material - Machining</b>	High Speed Steel
<b>Finish - Machining</b>	Black Oxide
<b>Drill Bit Point Angle</b>	118 Degrees
<b>Drill Bit Point Type</b>	Conventional Point
<b>Coolant Fed</b>	Non-Coolant Through
<b>Flute Type</b>	Spiral
<b>Number of Flutes</b>	2
<b>Flute Length</b>	3 7/8 in
<b>Maximum Drilling Depth</b>	1 5/8 in
<b>Helix Angle</b>	28 Degrees
<b>Cutting Direction</b>	Right Hand
<b>Spiral Direction</b>	Right Hand
<b>Shank Type - Machining</b>	Straight
<b>Shank Dia.</b>	25/64 in
<b>Shank Length</b>	1 3/8 in
<b>Overall Length</b>	5 1/4 in

<b>Depth:Dia. Ratio</b>	4xD
<b>Drill Length Class</b>	Jobber Length
<b>Drill Point Length</b>	0.122 in
<b>Drill Bit Grouping</b>	Individual
<b>Series</b>	150
<b>Standards</b>	DIN 338
<b>Drill Diameter Tolerance</b>	+0.0000 in /-0.0010 in
<b>Material Grade - Machining</b>	General Purpose
<b>Primary Material Application</b>	Cast Iron, Steel
<b>Primary Material Application ISO Code</b>	K, P
<b>Weight</b>	0.06 KG
<b>Weight</b>	0.06 KG