



Specifications

Material	Alloy Steel
Finish	Black Oxide
Drive Size	1/2 in
Impact Rated	Yes
Socket Depth	Standard
Socket Shape	6-Point
Includes Standard Sockets	Yes
Standard Socket Style	Size / Standard 6-Point: 10 mm, 11 mm, 12 mm, 13 mm, 14 mm, 15 mm, 16 mm, 17 mm, 18 mm, 19 mm, 20 mm, 21 mm, 22 mm, 23 mm, 24 mm, 25 mm, 26 mm, 27 mm, 28 mm, 29 mm, 30 mm, 32 mm, 33 mm, 34 mm, 35 mm, 36 mm
Standard Socket Count	Style / (26) 6-Point
Includes Deep Sockets	No
Deep Socket Count	Style / None
Drive Type	Impact
Socket Size	10 mm, 11 mm, 12 mm, 13 mm, 14 mm, 15 mm, 16 mm, 17 mm, 18 mm, 19 mm, 20 mm, 21 mm, 22 mm, 23 mm, 24 mm, 25 mm, 26 mm, 27 mm, 28 mm, 29 mm, 30 mm, 32 mm, 33 mm, 34 mm, 35 mm, 36 mm
Compatible Fastener Type	Bolts
Container Type	Plastic Case
Measurement Type	Metric
Non-Magnetic	No

Number of Pieces	26
Socket Size Range	10 to 36 mm
Standards	ANSI B107.2-2002
Tether Ready	No
Container Features	Dust Resistant
Container LxWxH	17 in x 12 29/32 in x 3 19/64 in
Includes	Blow Molded Case
Insulated	No
Locking	No
Non-Sparking	No
Weight	6.03 KG
Weight	6.03 KG