



Specifications

|                               |                 |
|-------------------------------|-----------------|
| Fitting Compatibility         | Schedule 80     |
| Gravity Flow                  | No              |
| Inside Diameter               | 1 in            |
| Material                      | Stainless Steel |
| Material Grade                | 316             |
| Maximum Operating Pressure    | 250 psi         |
| Maximum Operating Temperature | 450 Degrees F   |
| Metal Pipe Construction       | Seamless        |
| Minimum Operating Temperature | -60 Degrees F   |
| Nominal Pipe Size             | 1 in            |
| Outside Diameter              | 1 5/16 in       |
| Overall Length                | 6 in            |
| Schedule                      | Schedule 80     |
| Side A Connection Type        | Threaded        |
| Side A Gender                 | Male            |
| Side A Thread Type            | NPT             |
| Side B Connection Type        | Threaded        |
| Side B Gender                 | Male            |
| Side B Thread Type            | NPT             |

|                             |                                    |
|-----------------------------|------------------------------------|
| <b>Standards</b>            | ASME B1.20.1, ASTM A312, ASTM A733 |
| <b>Thread Configuration</b> | Threaded on Both Ends              |
| <b>Wall Thickness</b>       | 0.161 in                           |
| <b>Weight</b>               | 0.45 KG                            |
| <b>Weight</b>               | 0.45 KG                            |