

	<p><b>WESTWARD</b></p> <p><b>Micrometer Torque Wrench, Foot-Pound/Newton-Meter, 3/8 inch Drive Size, 15 ft-lb to 80 ft-lb</b></p> <p>Brand: Westward SKU: 6PAH9 Warranty:</p>
---	---

Specifications

Torque Measurement Type	Foot-Pound, Newton-Meter
Drive Size	3/8 in
Torque Range	15 ft-lb to 80 ft-lb
Torque Increments	0.5 ft-lb, 0.7 N-m
Primary Scale Minimum Torque	15 ft-lb
Primary Scale Maximum Torque	80 ft-lb
Head Type	Standard
Secondary Scale Minimum Torque	111.7 N-m
Secondary Scale Maximum Torque	23.7 N-m
Ratcheting	Yes
Rotation	Clockwise and Counterclockwise
Tether Style	Tether Capable
Nonsparking	No
Calibration Certificate Included	Yes
Torque Limiting Mechanism	Click-Type
Torque Setting	Adjustable
Visual	Audible Indicators / Audible Click
Material	Alloy Steel, Aluminum
Handle Type	Kurled

<b>Min. Arc Swing</b>	5 Degrees
<b>Min. Number of Cycles</b>	5,000
<b>Number of Geared Teeth</b>	72
<b>Overall Length</b>	16 in
<b>Includes</b>	(1) Case
<b>Standards</b>	ANSI B107.14 Torque Measurement Type / Foot-Pound, Newton-Meter
<b>Drive Size</b>	3/8 in
<b>Torque Range</b>	15 ft-lb to 80 ft-lb
<b>Torque Increments</b>	0.5 ft-lb, 0.7 N-m
<b>Primary Scale Minimum Torque</b>	15 ft-lb
<b>Primary Scale Maximum Torque</b>	80 ft-lb
<b>Head Type</b>	Standard
<b>Secondary Scale Minimum Torque</b>	111.7 N-m
<b>Secondary Scale Maximum Torque</b>	23.7 N-m
<b>Ratcheting</b>	Yes
<b>Rotation</b>	Clockwise and Counterclockwise
<b>Tether Style</b>	Tether Capable
<b>Nonsparking</b>	No
<b>Calibration Certificate Included</b>	Yes
<b>Torque Limiting Mechanism</b>	Click-Type
<b>Torque Setting</b>	Adjustable
<b>Visual</b>	Audible Indicators / Audible Click
<b>Material</b>	Alloy Steel, Aluminum
<b>Handle Type</b>	Kurled
<b>Min. Arc Swing</b>	5 Degrees
<b>Min. Number of Cycles</b>	5,000
<b>Number of Geared Teeth</b>	72
<b>Overall Length</b>	16 in
<b>Includes</b>	(1) Case
<b>Standards</b>	ANSI B107.14
<b>Weight</b>	1.4 KG
<b>Weight</b>	1.4 KG