



**GRAINGER**

**Nipple: 316 Stainless Steel, 1/2 in Nominal Pipe Size, 6 in Overall Lg, Threaded on Both Ends**

**Brand:** Grainger Approved  
**SKU:** 733-060XSGR  
**Warranty:** 0

#### Specifications

|                               |                                         |
|-------------------------------|-----------------------------------------|
| Application                   | Air, Natural Gas, Propane, Steam, Water |
| Fitting Compatibility         | Schedule 80                             |
| Gravity Flow                  | No                                      |
| Inside Diameter               | 9/16 in                                 |
| Material                      | Stainless Steel                         |
| Material Grade                | 316                                     |
| Maximum Operating Pressure    | 250 psi                                 |
| Maximum Operating Temperature | 450 Degrees F                           |
| Metal Pipe Construction       | Seamless                                |
| Minimum Operating Temperature | -60 Degrees F                           |
| Nominal Pipe Size             | 1/2 in                                  |
| Outside Diameter              | 13/16 in                                |
| Overall Length                | 6 in                                    |
| Schedule                      | Schedule 80                             |
| Side A Connection Type        | Threaded                                |
| Side A Gender                 | Male                                    |
| Side A Thread Type            | NPT                                     |
| Side B Connection Type        | Threaded                                |
| Side B Gender                 | Male                                    |

|                      |                                    |
|----------------------|------------------------------------|
| Side B Thread Type   | NPT                                |
| Standards            | ASME B1.20.1, ASTM A312, ASTM A733 |
| Thread Configuration | Threaded on Both Ends              |
| Wall Thickness       | 0.13 in                            |
| Weight               | 0.22 KG                            |
| Weight               | 0.22 KG                            |