



Specifications

Air Consumption	15 cfm
Air Inlet	1/4 in NPT
Air Pressure	90 psi
Max. Air Pressure	90 psi
Min. Air Pressure	90 psi
Min. Hose Size	3/8 in
Exhaust Location	Bottom
Duty Rating	General Duty
Breakaway Torque	200 ft-lb
Fastening Torque	190 ft-lb
Free Speed	9,600 RPM
Impact Rated	Yes
Impact Sound Level	102 dB
Impacts per Minute	1,680
Number of Speed Settings	3
Power to Weight Ratio	64.5 ft-lb/lb
Max. Bolt Capacity	1/2 in
Drive Size	3/8 in Square
Drive Type	Standard

Retainer Type	Friction Ring
Clutch Style	Pin Clutch
Tool Style	Compact
Vibration Level	4.4 m/sq sec
Overall Length	5 3/4 in
Handle Material	Aluminum
Housing Material	Aluminum
Handle Type	Pistol Grip
Features	360 Degrees Swivel Air Inlet, Curved Handle With Thermo-Plastic Rubber Injected In Housing For A Durable And Comfortable Grip, Resistant To Most Chemicals Used In Workshops, Single Handed Push Button Forward and Reverse, Teasing Trigger
Tool Weight	3.1 lb
Standards	EN ISO 11148-6:2013, ISO-28927-2
Weight	1.40 KG
Weight	1.40 KG