



HiKOKI

Rotary Hammer, 3 Modes, SDS Plus, Concrete 26mm, 830W, 0~1100rpm, 2.8kg

Brand: Hikoki

SKU: DH26PC2W1Z

Warranty: 24

- 830W motor for strong and reliable performance
- 3-mode operation for maximum versatility
- 2.9 J impact energy for efficient drilling
- Variable speed control for precise handling
- SDS-Plus system for quick bit replacement

Specifications

Rated input power	830 W
Voltage	230 V
Mains frequency	50/60 Hz
Impact energy (EPTA)	2.9 J
No load speed	0-1100 /min
Full load impact rate	0-4300 /min
Drill diameter concrete	3.4 - 26 mm
Drill diameter mild steel	13 mm
Drill diameter wood	32 mm
Tool weight	2.8 kg
Cable length	3.5 m
Tool length	349 mm
Tool width	83 mm
Tool height	199 mm
Application	Full Load Drilling into Concrete
Vibration	14.7 m/sec ²
Vibration uncertainty K	1.5 m/sec ²
Application	Full Load Chiselling
Vibration	14 m/sec ²

Vibration uncertainty K	1.5 m/sec ²
Emission sound pressure	94 dB
Emission sound power	102 dB
Emission uncertainty KpA	3 dB
Right	left rotation / Yes
Slip clutch	Yes
Lock-on function	Yes
Weight	2.8 KG
Weight	2.8 KG