



**Specifications**

|                               |   |
|-------------------------------|---|
| Thread Gender                 | Female to Male  |
| Trade Size                    | 1 1/2 in, 2 in, 1 1/2 in, 2 in  |
| Compatible Conduit Type       | IMC, Threaded RMC   |
| Compatible Conduit Trade Size | 1 1/2 in, 2 in  |
| Ends - Hazardous Fittings     | 1 1/2 in FNPT x 2 in MNPT   |
| Overall Length                | 31/32 in  |
| Weight                        | 0.38 lb   |
| Material                      | Steel   |
| Finish                        | Electroplated   |
| Hazardous Location Rating     | 2, B, Class III, Class II, Class I, C, Division 1 and 2, D, F, Groups A, Groups E, Groups IIA, G, IIB, IIC + H2, Zone 1 and |
| Series                        | RB  |
| For Use With                  | IMC, Threaded Conduit   |
| Conduit Fitting Type          | Reducing Bushing  |
| Connection Orientation        | Straight  |
| Fitting Type                  | Reducing Bushing  |
| Application                   | Designed to Reduce Conduit Entries to a Smaller Size and For Use In Threaded Rigid and IMC Conduit Systems                  |
| Body Style                    | RDC Bush  |
| Color                         | Silver  |

|                         |  |
|-------------------------|--|
| <b>Connection Type</b>  | Threaded   |
| <b>Insulated</b>        | Yes  |
| <b>Number of Pieces</b> | 1  |
| <b>Reduction Size</b>   | 2 in to 1 1/2 in   |
| <b>Standards</b>        | CSA C22.2 No. 25, CSA C22.2 No. 30, CSA Certified File 065181, UL 1203: 886, UL Listed File E34997 |
| <b>Thread Type</b>      | NPT  |
| <b>Weight</b>           | 0.18 KG  |
| <b>Weight</b>           | 0.18 KG  |