Contact: 0552822719
sales@aptools.sa
Al Shati, Dammam, Saudi Arabia



GRAINGER

## Reducing Bushing, Hazardous Location, Steel, 1 1/4 Inch_1/2 Inch Trade Size

**Brand:** Grainger Approved
**SKU:** RB125-50
**Warranty:** 0

**Specifications**

| | |
|---|---|
| **Thread Gender** | Female to Male |
| **Trade Size** | 1/2 in, 1 1/4 in, 1/2 in, 1 1/4 in |
| **Compatible Conduit Type** | IMC, Threaded RMC |
| **Compatible Conduit Trade Size** | 1/2 in, 1 1/4 in |
| **Ends - Hazardous Fittings** | 1/2 in FNPT x 1 1/4 in MNPT |
| **Overall Length** | 13/16 in |
| **Weight** | 0.29 lb |
| **Material** | Steel |
| **Finish** | Electroplated |
| **Hazardous Location Rating** | Class I, Division 1 and 2, Groups A, B, C, D, Zone 1 and, 2, Groups IIA, IIB, IIC, Class II, Groups E, F, G, Class III |
| **Series** | RB |
| **For Use With** | IMC, Threaded Conduit |
| **Conduit Fitting Type** | Reducing Bushing |
| **Connection Orientation** | Straight |
| **Fitting Type** | Reducing Bushing |
| **Application** | Designed to Reduce Conduit Entries to a Smaller Size and For Use In Threaded Rigid and IMC Conduit Systems |
| **Body Style** | RDC Bush |
| **Color** | Silver |

| | |
|---|---|
| **Connection Type** | Threaded |
| **Insulated** | Yes |
| **Number of Pieces** | 1 |
| **Reduction Size** | 1 1/4 in to 1/2 in |
| **Standards** | CSA C22.2 No. 25, CSA C22.2 No. 30, CSA Certified File 065181, UL 1203: 886, UL Listed File E34997 |
| **Thread Type** | NPT |
| **Weight** | 0.14 KG |
| **Weight** | 0.14 KG |