Contact: 0552822719
sales@aptools.sa
Al Shati, Dammam, Saudi Arabia



Finish Thompson

Air Operated Drum Pump, Basic Pump with Discharge Hose, For Container Type Drum

Brand: Finish Thompson
SKU: EFP-40 & S4 Kit
Warranty: 0

Specifications

Pump Package Type	Basic Pump with Discharge Hose
Air Inlet Size	1/4 in MNPT
Air Outlet Size	1/4 in
For Container Size	55 gal
For Container Type	Drum
Max. Flow Rate	15 gpm
Max. Oil Flow	5 gpm
Max. Viscosity	300 cps
Discharge Connection Type	Hose Barb
Discharge Tube Outlet ID	3/4 in
Discharge Tube Outlet OD	1 in
Min. Air Pressure	40 psi
Max. Air Pressure	40 psi
Compatible Chemicals	Acetic Acid 20%, Acetic Acid 80%, Ammonium Hydroxide, Antifreeze (Coolant), Calcium Chloride, Citric Acid 50%, Deionized Water, Ethylene Glycol, Formic Acid, Fresh Water, Phosphoric Acid (40% Solution), Potassium Hydroxide (50%), Salt Water, Sodium Bicarbonate (10%), Sodium Bisulfate, Sodium Bisulfite, Sodium Hydroxide/Caustic Soda (20%), Sodium Hydroxide/Caustic Soda (50%), Sodium Hydroxide/Caustic Soda (80%)

Not Recommended Chemicals	Acetic Acid (Glacial), Acetone, Ammonia (Liquids), Anhydrous Ammonia, Automatic Transmission Fluid, Biodiesel, Brake Fluid, Chromic Acid 10%, Chromic Acid 30%, Chromic Acid 5%, Chromic Acid 50%, Cyclohexane, DEF, Diesel Fuel, E85, Ethyl (Ethanol), Ethyl Acetate, Formaldehyde, Formaldehyde 40%, Gasoline, Glycerin, Heptane, Hexane, Hydraulic Oils (Petroleum), Hydraulic Oils (Synthetic), Hydrazine, Hydrochloric/Muriatic Acid (100%), Hydrochloric/Muriatic Acid (20%), Hydrochloric/Muriatic Acid (37%), Hydrofluoric Acid (20%), Hydrofluoric Acid (75%), Hydrofluoric Acid 100%, Isopropyl (Isopropanol), Kerosene, Lacquer Thinners, Methyl (Methanol), Methyl Ethyl Ketone (MEK), Naphtha, Nitric Acid (10% Solution), Nitric Acid (20% Solution), Nitric Acid (50% Solution), Nitric Acid (Concentrated Solution), Paint Thinner, Sodium Hypochlorite/Bleach (to 20%), Stoddard Solvent (Mineral Spirits), Sulfuric Acid (10% - 75%), Sulfuric Acid (75% - 100%), Sulfuric Acid (to 10%), Toluene, Trichlorethylene (50%), Turpentine, Windshield Washer Fluid, Xylene
Max. Head - Pumps	17 ft
Max. Head Pressure	7.4 psi
Min. Fluid Temp.	0 Degrees F
Max. Fluid Temp.	150 Degrees F
Motor HP	1/2 hp
Motor RPM	11,000 RPM
Duty Cycle	Continuous
Seal Material	FKM
Power Source	Air
Variable Speed	Yes
Noise Level	78 db
Pump Connection ID	1 1/4 in
Pump Connection OD	1 1/4 in
Includes Discharge Hose	Yes
Hose Inside Dia.	3/4 in
Hose Outside Dia.	1 in
Hose Length	60 in
Hose Tube Material	PVC
Housing Material - Pumps	Polypropylene
Includes Suction Tube	Yes
Suction Tube Length	40 in
Suction Tube Material	Polypropylene
Suction Tube ID	1 1/4 in
Suction Tube OD	1 1/4 in
Adapter Material	Polypropylene
Overall Length	46 13/16 in
Height Above Container	6 7/8 in
Self-Priming	Yes

Diesel Exhaust Fluid Compatible	No
For Use With	Chemicals
Includes	Clamp, Hose, Motor, Pump
Explosion Proof	Yes
Wetted Materials	316SS & PVC, FKM, PP, PTFE
Series	EF
For Media Type	Acetic Acid, Ammonium Hydroxide, Antifreeze, Calcium Chloride, Citric Acid, Ethylene Glycol, Formic Acid, Phosphoric Acid (40% Solution), Potassium Hydroxide (50%), Sodium Bicarbonate, Sodium Bisulfate, Sodium Bisulfite, Sodium Hydroxide, Water
Weight	4.4 KG
Weight	4.4 KG