APTOOLS
Arab Pros For Machinery & Equipment

Product Catalog
2026-11-04 10:25 AM
www.aptools.sa

Contact: 0552822719
sales@aptools.sa
Al Shati, Dammam, Saudi Arabia



Appleton

Reducing Bushing, Hazardous Location, Iron, 3 1/2 in_3 inch Trade Size

Brand: Appleton Electric
SKU: RB350-300
Warranty: 0

Specifications

Thread Gender	Female to Male
Trade Size	3 1/2 in, 3 in, 3 1/2 in, 3 in
Compatible Conduit Type	IMC, Threaded RMC
Compatible Conduit Trade Size	3 in, 3 1/2 in
Ends - Hazardous Fittings	3 in FNPT x 3 1/2 in MNPT
Overall Length	1 7/16 in
Weight	0.92 lb
Material	Iron
Finish	Chromate Coated, Electroplated, Powder Coated
Hazardous Location Rating	Class III, Class II, Class I, C, Division 1 and 2, D, F, Groups B, Groups E, Groups IIA, G, IIB + H2, Zone 1 and 2
Series	RB
For Use With	IMC, Threaded Conduit
Conduit Fitting Type	Reducing Bushing
Connection Orientation	Straight
Fitting Type	Reducing Bushing
Application	Designed to Reduce Conduit Entries to a Smaller Size and For Use In Threaded Rigid and IMC Conduit Systems
Body Style	RDC Bush
Color	Silver

Connection Type	Threaded
Insulated	Yes
Number of Pieces	1
Reduction Size	3 1/2 in to 3 in
Standards	CSA C22.2 No. 25, CSA C22.2 No. 30, CSA Certified File 065181, UL 1203: 886, UL Listed File E34997
Thread Type	NPT
Weight	0.34 KG
Weight	0.34 KG