



**Specifications**

<b>Compatible with Model</b>	17, 17F, 17FV, 17FVB, 17HP, 17HPV, 17V, 18, 18-90, 18HP, 18P, 18V, 20, 20F, 20H-320-25R, 20HP, 20P, 22A, 22B, 25, 26, 26F, 26FV, 26FVB, 26HP, 26HPV, 26V, 301251, 301253, 9, 9F, 9FVB, 9HP, 9P, 9V, 9VB, CS310A, HW-17, HW-17F, HW-17R, HW-18, HW-18R, HW-20, HW-20R, HW-25, HW-26, HW-26F, HW-26R, HW-9, HW-9F, HW-9R, PTA-17, PTA-17F, PTA-17FV, PTA-17V, PTA-26, PTA-26F, PTA-26FV, PTA-26V, PTA-9, PTA-9F, PTW-18, PTW-20, WP-17, WP-17-PSH, WP-17F, WP-17FV, WP-17V, WP-17V-PSH, WP-18, WP-18SC, WP-18V, WP-20, WP-20P, WP-20V, WP-25, WP-9, WP-9F, WP-9FV, WP-9V, WP-R17F, WP-R17FV, WP-R9F, WP-R9FV
<b>Compatible with Series</b>	17, 18, 20, 20H-320, 20P, 22, 25, 26, 9, A-125, A-150, A-200, A-250, HW-17, HW-18, HW-20, HW-25, HW-26, HW-9, PTA-17, PTA-26, PTA-9, PTW-18, PTW-20, W-200, W-225, W-250, W-280, W-310, W-350, W-375, W-410
<b>For Maximum Electrode Diameter</b>	1 in
<b>Material</b>	Alumina
<b>Nozzle Nominal Size</b>	No. 6
<b>Reference Number</b>	13N10
<b>TIG Torch Application</b>	Non-Gas Lens, Stubby Non-Gas Lens
<b>Type</b>	Standard Nozzle
<b>Welding Processes</b>	TIG Welding (GTAW)
<b>Compatible with Brand</b>	Miller
<b>Compatible with Grainger Part Number</b>	48VF53, 48VF60, 6UHL8, 6XXN2, 6XXN3, 6XXN4, 6XXN5, 6XXN6, 6XXN8, 6XXN9, 6XXP0, 6XXP1, 6XXP2, 6XXP3, 6XXP4, 6XXP5, 6XXP6, Not Found
<b>Outside Diameter</b>	#6 (3/8 in)
<b>Nozzle Length</b>	Standard
<b>Sub-Brand</b>	Weldcraft
<b>Weight</b>	0.09 KG

Weight	0.09 KG
--------	---------