



Specifications

|                                  |                                      |
|----------------------------------|--------------------------------------|
| Pipe Fitting Material            | 304 Stainless Steel, Stainless Steel |
| Material Grade                   | 304                                  |
| Class                            | Class 150                            |
| For Pipe Schedule                | 40                                   |
| Fitting Side A Nominal Pipe Size | 1/4 in                               |
| Fitting Side A Gender            | Female                               |
| Fitting Side A Type              | NPT                                  |
| Fitting Side A Outside Diameter  | 1/4 in                               |
| Fitting Side A Pipe Threading    | 18                                   |
| Fitting Side B Nominal Pipe Size | 1/4 in                               |
| Fitting Side B Gender            | Female                               |
| Fitting Side B Type              | NPT                                  |
| Fitting Side B Outside Diameter  | 1/4 in                               |
| Fitting Side B Pipe Threading    | 18                                   |
| Fitting Side C Nominal Pipe Size | 1/4 in                               |
| Fitting Side C Gender            | Female                               |
| Fitting Side C Type              | NPT                                  |
| Fitting Side C Outside Diameter  | 1/4 in                               |
| Maximum Operating Pressure       | 300 psi                              |

|  |  |
|--|--|
| <b>Max. Steam Pressure</b>                 | 150 psi  |
| <b>Includes Pre-Applied Thread Sealant</b> | No   |
| <b>Includes Seal</b>                       | No   |
| <b>Overall Length</b>                      | 29 mm  |
| <b>Color</b>                               | Silver   |
| <b>Application</b>                         | Air, Natural Gas, Non-Potable Water, Oil, Potable Water, Steam |
| <b>Standards</b>                           | ASME B1.20.1, ASTM A351, MSS SP-114                            |
| <b>Weight</b>                              | 0.06 KG  |
| <b>Weight</b>                              | 0.06 KG  |