



IR Ingersoll Rand

Air Powered, Impact Wrench, 90 psi, 550 ft-lb Fastening Torque 1UMK7

Brand: Ingersoll Rand
SKU: 2135PTIMAX
Warranty: 0

Specifications

Air Consumption	24 cfm
Air Inlet	1/4 in NPT
Air Pressure	90 psi
Max. Air Pressure	100 psi
Min. Air Pressure	90 psi
Min. Hose Size	3/8 in
Exhaust Location	Bottom
Duty Rating	Industrial Duty
Breakaway Torque	780 ft-lb
Fastening Torque	550 ft-lb
Free Speed	11,000 RPM
Impact Rated	Yes
Impact Sound Level	94 dB
Impacts per Minute	1,250
Number of Speed Settings	4
Power to Weight Ratio	200 ft-lb/lb
Max. Bolt Capacity	1/2 in
Drive Size	1/2 in Square
Drive Type	Standard

Retainer Type	Pin Detent
Clutch Style	Twin Hammer
Tool Style	Full-Size
Vibration Level	13.3 m/sq sec
Overall Length	7 1/2 in
Handle Material	Composite
Housing Material	Composite
Handle Type	Pistol Grip
Tool Brand	Ingersoll Rand
Features	Durability, Reliability
Tool Weight	3.9 lb
Standards	ISO 11148, ISO 15744, ISO 28927
Weight	1.76 KG
Weight	1.76 KG