

	<p>IR Ingersoll Rand</p> <p>Air Powered, Impact Wrench, 90 psi, 1,100 ft-lb Fastening Torque 13E913</p> <p>Brand: Ingersoll Rand SKU: 2145QiMAX Warranty: 0</p>
---	---

Specifications

Air Consumption	32 cfm
Air Inlet	1/2 in NPT Female
Air Pressure	90 psi
Max. Air Pressure	100 psi
Min. Air Pressure	90 psi
Min. Hose Size	1/2 in
Exhaust Location	Bottom
Duty Rating	Industrial Duty
Breakaway Torque	1,350 ft-lb
Fastening Torque	1,100 ft-lb
Free Speed	7,000 RPM
Impact Rated	Yes
Impact Sound Level	96 dB
Impacts per Minute	1,150
Number of Speed Settings	4
Power to Weight Ratio	182.4 ft-lb/lb
Max. Bolt Capacity	3/4 in
Drive Size	3/4 in Square
Drive Type	Standard

Retainer Type	Friction Ring, Through Hole
Clutch Style	Twin Hammer
Tool Style	Compact
Vibration Level	8.7 m/sq sec
Overall Length	8 1/2 in
Handle Material	Composite
Housing Material	Composite
Handle Type	Pistol Grip
Tool Brand	Ingersoll Rand
Features	Max Durability, Max Power, Max Productivity
Tool Weight	7.4 lb
Standards	EN ISO 11148-6, EN ISO 15744, EN ISO 28927-2
Weight	3.35 KG
Weight	3.35 KG