



Specifications

Pump Package Type	Unmetered Dispensing with Manual Shut-Off
Air Inlet Size	1/4 in FNPT
For Container Size	55 gal
For Container Type	Drum
Air Consumption	14 cfm
Max. Flow Rate	6 gpm
Max. Oil Flow	6 gpm
Discharge Connection Type	FNPT
Discharge Tube Outlet ID	1/2 in
Discharge Tube Outlet OD	13/16 in
Min. Air Pressure	40 psi
Max. Air Pressure	200 psi
Compatible Chemicals	Automatic Transmission Fluid, Gear Lube, Hydraulic Oils (Petroleum), Hydraulic Oils (Synthetic)
Not Recommended Chemicals	Diesel Fuel, Grease, Kerosene, Motor Oil
Ratio	5:1
Max. Outlet Pressure	1,000 psi
Min. Fluid Temp.	30 Degrees F
Max. Fluid Temp.	120 Degrees F

Seal Material	Buna-N
Power Source	Air
Pump Connection ID	1/2 in
Pump Connection Type	FNPT
Includes Discharge Hose	Yes
Hose Inside Dia.	1/2 in
Hose Outside Dia.	13/16 in
Housing Material - Pumps	Steel
Includes Suction Tube	Yes
Suction Tube Length	7 1/2 in
Suction Tube Material	Steel
Suction Tube OD	1 21/32 in
Includes Nozzle	Yes
Nozzle Operation	Manual
Nozzle Material	Steel
Self-Priming	Yes
Includes	Roll Around Base, Shut Off Valve
Wetted Materials	Brass, Buna-N, Steel
For Media Type	Automatic Transmission Fluid, Gear Lube, Hydraulic Oil
Weight	24 KG
Weight	24 KG