



Specifications

Build volume	74 x 132 x 175 mm (2.9 x 5.2 x 6.9 in)
Support	Mechanically removed - printed with the same material as the model
Light source	UV integrated light (wavelength 405 nm)
Connectivity	Wi-Fi, Ethernet, USB
Operating system	Android
Processor	Quad Core
Touchscreen	4" IPS 800 x 480
Available materials	Zortrax Resin BASIC, Zortrax Resin PRO, Zortrax Resin FLEXIBLE, Zortrax Resin DENTAL Model
External materials	Applicable
In the box	3D Printer, Z-SUITE, Starter Kit, Zortrax Photopolymer Resin BASIC (500 ml)
Printing	
Technology	UV LCD
Pixel size	50 microns (0.05 mm)
Layer thickness	25, 50, 100 microns
Print speed	20-36 mm/h
Ambient operation temperature	20-30° C (68-86° F)
Storage temperature	0-35° C (32-95° F)
AC input	110 V ~ 5.9 A 50/60 Hz 240 V ~ 2.5A 50/60 Hz
Power supply parameters	12 V DC @ 6 A, 50 W

Maximum power consumption	50 W
Ultrasonic Cleaner	
Capacity	3.2 l. (108.2 oz.)
Made of	stainless steel
Cleaning time control	0-30 min.
Automated Cleaning Device	
Weight	16.5 KG
Weight	16.5 KG