



Specifications

|                               |                                    |
|-------------------------------|------------------------------------|
| Fitting Compatibility         | Schedule 80                        |
| Inside Diameter               | 9/16 in                            |
| Material                      | Stainless Steel                    |
| Material Grade                | 316                                |
| Maximum Operating Pressure    | 3217 psi @ 650 Degrees F           |
| Maximum Operating Temperature | 650 Degrees F                      |
| Metal Pipe Construction       | Seamless                           |
| Minimum Operating Temperature | -20 Degrees F                      |
| Nominal Pipe Size             | 1/2 in                             |
| Outside Diameter              | 13/16 in                           |
| Overall Length                | 2 1/2 in                           |
| Schedule                      | Schedule 80                        |
| Side A Connection Type        | Threaded                           |
| Side A Gender                 | Male                               |
| Side A Thread Type            | NPT                                |
| Side B Connection Type        | Threaded                           |
| Side B Gender                 | Male                               |
| Side B Thread Type            | NPT                                |
| Standards                     | ASME B1.20.1, ASTM A312, ASTM A733 |

|                             |                       |
|-----------------------------|-----------------------|
| <b>Thread Configuration</b> | Threaded on Both Ends |
| <b>Wall Thickness</b>       | 0.13 in               |
| <b>Weight</b>               | 0.22 KG               |
| <b>Weight</b>               | 0.22 KG               |