



 **Appleton**

Enhanced Rating Cord Connector, Brass, 1 1/2 in MNPT, 1.22 in to 1.50 in, Silver

Brand: Appleton Electric
SKU: 50SA2F1505
Warranty: 0

Specifications

Body Color	Silver
Body Material	Brass, Brass
Cord Dia. Range	1.22 in to 1.50 in
Box Connection	1 1/2 in MNPT, 1 1/2 in MNPT
Connection Orientation	Straight
For Maximum Cable OD	1.5 in
For Minimum Cable OD	1.22 in
Hazardous Location Rating	Class I, Division 2, Groups B, C, D, Class II, Groups E, F, G, Class III
Hazardous Location Rating - Europe	Ex d I, Ex d IIC Gb, Ex d Imb, Ex e I, Ex e I mB, Ex e IIC Gb, Ex II 2 GD, II 1D, Ex II3G, Ex nR IIC GC I M2, Ex ta IIIC Da, Gas Groups IIA, IIB, IIC, Zone 1 and 2, Zone 21 and 22
Length - Box to End of Connector	1 1/8 in
Material - External Strain Relief	No External Strain Relief
Number of Cords	1
Strain Relief Type	No External Strain Relief
Environmental Rating	Hazardous Locations
Collar Material	Brass
Compatible Conduit Trade Size	1 1/2 in
For Use With	Unarmored Cable
Hub Size	1 1/2 in

Maximum Operating Temperature	266 Degrees F
Minimum Operating Temperature	-76 Degrees F
Sealing Ring Material	Thermoplastic Elastomer
Standards	101909, ANSI-ASME B1.20.1, CSA C22.2 No. 174, EN, IEC Standards 6007, IEC Standards 60079-0, IEC Standards 60079-1, IEC Standards 60079-7
Thread Size	1 1/2 in
Thread Type	NPT, NPT Thread
Weight	0.226796 KG
Weight	0.226796 KG