



**Fuse, Time Delay, Class RK5, FRS-R Series, 600 A**

**Brand:**  
**SKU:** FRS-R-600  
**Warranty:** 0

**Specifications**

|                                     |  |
|-------------------------------------|--|
| <b>Amps</b>                         | 600 A  |
| <b>AC Voltage Rating</b>            | 600V AC  |
| <b>DC Voltage Rating</b>            | 300V DC  |
| <b>Class</b>                        | RK5  |
| <b>Series</b>                       | FRS-R  |
| <b>Visual Indication</b>            | Nonindicating  |
| <b>Speed</b>                        | Time Delay   |
| <b>Body Style</b>                   | Blade  |
| <b>Fits Fuse Block Style</b>        | Rejection  |
| <b>Interrupt Rating</b>             | 200kA at 600V AC, 20kA at 300V DC                          |
| <b>Fuse Size</b>                    | 13-3/8 in L x 2-7/8 in dia                                 |
| <b>Length</b>                       | 13 3/8 in  |
| <b>Diameter</b>                     | 2 7/8 in   |
| <b>Equivalent Brand and Series</b>  | Bussmann FRS-R, Edison ECSR, Littelfuse FLSR, Mersen TRS-R |
| <b>Equivalent Series</b>            | ECSR, FLSR, FRS-R, TRS-R                                   |
| <b>Compatible Fuse Block Series</b> | 1BR, R600  |
| <b>Body Material</b>                | Fiberglass   |
| <b>Element</b>                      | Dual   |
| <b>Standards</b>                    | CE, CSA Certification Class 1422-01, UL 248-12 Guide JDDZ  |

|        |              |
|--------|--------------|
| Weight | 1.6329312 KG |
| Weight | 1.6329312 KG |