



|   |   |
|---|---|
|  |  <p><b>Micrometer Torque Wrench, Drive Size 3/8 in, Torque Range 16 ft-lb to 80 ft-lb 426F02</b></p> <p>Brand: Proto<br/>SKU: J6006C<br/>Warranty: 0</p> |
|---|---|

Specifications

|                              |                                    |
|------------------------------|------------------------------------|
| Torque Measurement Type      | Foot-Pound                         |
| Drive Size                   | 3/8 in                             |
| Torque Range                 | 16 ft-lb to 80 ft-lb               |
| Torque Increments            | 0.5 ft-lb                          |
| Primary Scale Minimum Torque | 16 ft-lb                           |
| Primary Scale Maximum Torque | 80 ft-lb                           |
| Head Type                    | Standard                           |
| Ratcheting                   | Yes                                |
| Rotation                     | Clockwise and Counterclockwise     |
| Torque Adjustability         | Adjustable                         |
| Clockwise Accuracy           | +/- 4%                             |
| Counterclockwise Accuracy    | +/- 6%                             |
| Corrosion Resistant          | Yes                                |
| Torque Limiting Mechanism    | Click-Type                         |
| Torque Setting               | Adjustable                         |
| Visual                       | Audible Indicators / Audible Click |
| Finish                       | Chrome                             |
| Material                     | Alloy Steel                        |
| Handle Type                  | Knurled                            |

|                               |                    |
|-------------------------------|--------------------|
| <b>Handle Material</b>        | Alloy Steel        |
| <b>Handle Color</b>           | Silver             |
| <b>Dual Scale</b>             | Yes                |
| <b>Min. Arc Swing</b>         | 15 Degrees         |
| <b>Min. Number of Cycles</b>  | 5,000              |
| <b>Number of Geared Teeth</b> | 24                 |
| <b>Overall Length</b>         | 15 in              |
| <b>Overall Width</b>          | 1 7/16 in          |
| <b>Includes</b>               | (1) Case           |
| <b>Standards</b>              | ASME B107.300-2010 |
| <b>Weight</b>                 | 3 lb               |
| <b>Head Movement</b>          | Ratcheting         |
| <b>Weight</b>                 | 1.360 KG           |
| <b>Weight</b>                 | 1.360 KG           |