





Dial Torque Wrench, Foot-Pound & Meter-Kilogram, 1/2 inch

Brand: Proto
SKU: J6125F
Warranty:

Specifications

Torque Measurement Type	Foot-Pound, Meter-Kilogram
Drive Size	1/2 in
Torque Range	50 to 250 ft-lb, 7 to 35 m-kg
Torque Increments	1 m-kg, 5 ft-lb
Overall Length	21 1/2 in
Extended Data Testing	Yes, NIST
Reset Type	Memory Needle
Primary Scale Minimum Torque	50 ft-lb
Primary Scale Maximum Torque	250 ft-lb
Secondary Scale Minimum Torque	7 m-kg
Secondary Scale Maximum Torque	35 m-kg
Clockwise Accuracy	+/-4%
Counterclockwise Accuracy	+/-4%
Handle Type	Plain
Head Material	Alloy Steel
Handle Color	Black
Handle Material	Rubber
Memory Needle	Yes
Finish	Chrome

Torque Adjustability	Adjustable
Visual	Audible Indicators / No
Measurement Type	SAE
Insulated	No
Corrosion Resistant	Yes
Nonsparking	No
Ratcheting	Yes
Calibration Certificate Included	Yes
Rotation	Clockwise and Counterclockwise
Standards	ASME B107.14M, ISO 6789, JIS B4650
Tether Style	Tether Capable
Extension Handles	No
Head Type	Standard
Includes	(1) Blow Molded Box
Min. Number of Cycles	5,500
Weight	3.8 lb
Weight	1.9 KG
Weight	1.9 KG