



Specifications

| | |
|--------------------------------------|--|
| Build volume | 74 x 132 x 175 mm (2.9 x 5.2 x 6.9 in) |
| Support | Mechanically removed - printed with the same material as the model |
| Light source | UV integrated light (wavelength 405 nm) |
| Connectivity | Wi-Fi, Ethernet, USB |
| Operating system | Android |
| Processor | Quad Core |
| Touchscreen | 4" IPS 800 x 480 |
| Available materials | Zortrax Resin BASIC, Zortrax Resin PRO, Zortrax Resin FLEXIBLE, Zortrax Resin DENTAL Model |
| External materials | Applicable |
| In the box | 3D Printer, Z-SUITE, Starter Kit, Zortrax Photopolymer Resin BASIC (500 ml) |
| Printing | |
| Technology | UV LCD |
| Pixel size | 50 microns (0.05 mm) |
| Layer thickness | 25, 50, 100 microns |
| Print speed | 20-36 mm/h |
| Ambient operation temperature | 20-30° C (68-86° F) |
| Storage temperature | 0-35° C (32-95° F) |
| AC input | 110 V ~ 5.9 A 50/60 Hz 240 V ~ 2.5A 50/60 Hz |

| | |
|----------------------------------|---------------------|
| Power supply parameters | 12 V DC @ 6 A, 50 W |
| Maximum power consumption | 50 W |
| Weight | 16.5 KG |
| Weight | 16.5 KG |