



**Specifications**

<b>Thread Gender</b>	Female to Male
<b>Trade Size</b>	1 1/2 in, 2 in, 1 1/2 in, 2 in
<b>Compatible Conduit Type</b>	IMC, Threaded RMC
<b>Compatible Conduit Trade Size</b>	1 1/2 in, 2 in
<b>Ends - Hazardous Fittings</b>	1 1/2 in FNPT x 2 in MNPT
<b>Overall Length</b>	31/32 in
<b>Weight</b>	0.38 lb
<b>Material</b>	Steel
<b>Finish</b>	Electroplated
<b>Hazardous Location Rating</b>	2, B, Class III, Class II, Class I, C, Division 1 and 2, D, F, Groups A, Groups E, Groups IIA, G, IIB, IIC + H2, Zone 1 and
<b>Series</b>	RB
<b>For Use With</b>	IMC, Threaded Conduit
<b>Conduit Fitting Type</b>	Reducing Bushing
<b>Connection Orientation</b>	Straight
<b>Fitting Type</b>	Reducing Bushing
<b>Application</b>	Designed to Reduce Conduit Entries to a Smaller Size and For Use In Threaded Rigid and IMC Conduit Systems
<b>Body Style</b>	RDC Bush
<b>Color</b>	Silver

<b>Connection Type</b>	Threaded
<b>Insulated</b>	Yes
<b>Number of Pieces</b>	1
<b>Reduction Size</b>	2 in to 1 1/2 in
<b>Standards</b>	CSA C22.2 No. 25, CSA C22.2 No. 30, CSA Certified File 065181, UL 1203: 886, UL Listed File E34997
<b>Thread Type</b>	NPT
<b>Weight</b>	0.18 KG
<b>Weight</b>	0.18 KG