




Light Tower Metal HiLight, 2 cylinder engine

Brand: Atlas Copco

SKU: V4

Warranty:

Specifications

Performance Data	
Rated Frequency Hz	50 Hz - 60 Hz
Rated Voltage V	230 - 240/120
Rated Power (PRP) kW	5,4 - 6,8
Operating Temperature (min)	max) oC / -10/49 -10/49
Sound Power @ 7m (LPA) dB(A)	71 - 73
Engine - Kubota	
Model	Z482
Speed rpm	3.000 - 3.600
Rated Net Output (PRP) kW	6,9 - 8,1
Coolant	Liquid cooled diesel
Number of cylinders	2
Alternator - Sincro	
Model	EK 2 MCT
Rated Output kVA	6 - 7,5
Insulation	Enclosure protection class/IP / H/23
Consumption	
Fuel tank capacity liter	105

Runtime before refueling @ 4kW Load hrs	57 - 50
Battery	45 Ah, 390 CCA
Power Output	
Aux Power MCCB kW	1,4 - 2
Lights	
Floodlights	4 x Metal Halide
Wattage W	4 x 1.000
Luminosity	5,4lm/m ² @ 28.328m ² (0.5fc @ 7 acres)
Manual mast	
Type	Vertical, 5 section with
Rotation degrees	360
Maximum Height m	7,5
Maximum Speed Wind kph	80
Construction	
Traier	Unibody trailer with 4 point leveling system
Tires	155R13
Tow Hitch	2 inch ball / pintle combo
Base Frame	Fluid containment system with external drain system
Enclosure	Gull-wing HardHat doors
Dimensions and weigth	
Dimensions in transport (LxWxH) m	1,67 x 1,10 x 2,50
Dimensions in operation (LxWxH) m	2,90 x 2,31 x 7,54
Weight kg	694
Weight	694 KG
Weight	694 KG