Contact: 0552822719
sales@aptools.sa
Al Shati, Dammam, Saudi Arabia



Atlas Copco

Dewatering Pump with vacuum pump, Max. flow 340 m3/hour & Max. head 27 m with Diesel Engine

Brand: Atlas Copco
SKU: WEL 6-250
Warranty:

Specifications

Qmax	340 m3/h - 5.670 l/min (1,500 USgpm)
Hmax	27,5 m (90 ft)
Q max eff.	240 m3/h - 4.000 l/min (1,100 USgpm)
Eff. max	62 %
Suction port	Flanged - DN 150 D.I. 1882 (6")
Delivery port	Flanged - DN 150 D.I. 1882 (6")
Impeller type	Semi-Open, 2 vane
Solids handling	76 mm (3.0 ")
Material	S275JR EN 10025-2 carbon steel
Coatings	Epoxy powder, average thickness of 80 µm
Color	Yellow and grey Atlas Copco (standard)
Features	Modular and demountable framework; hot dip galvanised steel support bases, bullbars and lifting beam. Mudguards with galvanised steel walkable surface. Tow bar, adjustable support feet. Lockable battery box. Fuel level indicator.
Battery	Acid charge Pb-Ca maintenance free
12 V - 100 Ah - 400 A	
Tank	300 l (79.3 USG)
Locking keys	Fuel cap
Dimensions	1410 x 2330 x 1880 mm
56 x 92 x 74 "	

H suction port	1,17 m (3.8 ft)
Weight (KL10)	1120 kg (2,470 lb)
Weight (ZD35)	1130 kg (2,490 lb)
Weight	1130 KG
Weight	1130 KG